NSN 5930-01-046-6549

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-046-6549

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Salt spray resistant and shock resistant and vibration resistant
Body Diameter:
0.625 inches
Bushing Length:
0.500 inches
Body Length:
0.820 inches
Actuator Diameter:
0.370 inches
Actuator Height:
0.430 inches
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 tab, solder lug
Specification Data:
06481-935249-31 manufacturers specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-01-046-6549Push Switch - Page 2 of 2



Fiig:

A053a0