

View Online at <https://aerobasegroup.com/nsn/5930-01-046-6953>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof and shock proof

Bushing Length:

0.469 inches

Body Length:

0.572 inches

Body Width:

0.364 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.687 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Helicopter, search and rescue, hh-60h; tactical air opns module (an/tyq (23) ; aircraft, airlifter c-17a; forrestal class cv; arleigh burke class ddg; wasp class lhd; emory s. Land class as; nimitz class cvn; tarawa class lha

Mounting Surface To Terminal End Distance:

0.750 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

Special Features:

Weapon system essential

Precious Material And Location:

Terminals gold and contact surfaces silver

Test Data Document:

81349-mils8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 printed circuit

Specification Data:

96906-ms21356 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0