NSN 5930-01-046-9310

Toggle Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-046-9310

| Bushing mount |
|--|
| Overall Length: |
| 0.500 inches |
| Overall Height: |
| 1.265 inches |
| Overall Width: |
| 0.270 inches |
| Bushing Length: |
| 0.350 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.270 inches |
| Body Height: |
| 0.350 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.115 inches |
| Actuator Height: |
| 0.410 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position momentary |
| Maximum Voltage Rating In Volts: |
| 20.0 ac and 20.0 dc |
| Mounting Surface To Terminal End Distance: |
| 0.505 inches |
| Inclosure Type: |
| Fully enclosed |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 400.000 milliamperes resistive ac

Precious Material And Location:

Contact surfaces gold and body surface gold

NSN 5930-01-046-9310 Toggle Switch - Page 2 of 2



| inread Series Designator: |
|-----------------------------|
| Uns |
| Terminal Type And Quantity: |
| 3 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0