

View Online at <https://aerobasegroup.com/nsn/5930-01-047-1656>

Inside Diameter:

0.750 inches single connection

Thread Length:

2.250 inches single pressure connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.000 inches

Overall Height:

2.812 inches

Overall Width:

2.125 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

2.750 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

14 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

2500.00 pounds per square inch

Thread Size:

0.750 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+3.00/+600.00 actuation point pounds per square inch and +2.00/+596.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0