

View Online at <https://aerobasegroup.com/nsn/5930-01-047-4754>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

1.288 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.094 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Overall Diameter:**

0.500 inches

**Nonturn Device Radius:**

0.102 inches at 9: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 1: 30 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

3 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

50.0 milliamperes resistive load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0