

View Online at <https://aerobasegroup.com/nsn/5930-01-047-6370>

Thread Class:

3b single pressure connection

Thread Length:

0.360 inches single pressure connection

Overall Length:

2.000 inches

Body Diameter:

1.120 inches

Overall Diameter:

1.120 inches

Pressure Switch Type:

Gage

Mounting Method:

Input port

Thread Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

250.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.0 amperes resistive load single voltage and 4.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

10.00 actuation point pounds per square inch gage and 4.00 deactuation point pounds per square inch gage and 4.00 differential point pounds per square inch gage and 6.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

32.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Thread Series Designator:

Unef single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0