

View Online at <https://aerobasegroup.com/nsn/5930-01-047-6377>

Overall Length:

1.203 inches

Overall Height:

0.411 inches

Body Diameter:

0.605 inches

Mounting Slot Width:

0.140 inches

Body Height:

0.290 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance Between Mounting Facility Centers:

0.937 inches

Temperature Sensing Element Type:

Disc

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit

Mounting Method:

Bracket and slot and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

7.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-30.00/+500.00 actuation point degrees fahrenheit and -25.00/+495.00 deactuation point degrees fahrenheit

Contact Stimulus Rating:

195.00 actuation point degrees fahrenheit and 183.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 ac at sea level third voltage

Media For Which Designed:

Gas or liquid

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0