

View Online at <https://aerobasegroup.com/nsn/5930-01-047-6395>

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

1.270 inches

Body Width:

0.635 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.180 inches

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 4.000 amperes lamp dc and 15.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 turret

Specification Data:

96906-ms27734 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0