

View Online at <https://aerobasegroup.com/nsn/5930-01-047-7018>

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

Between 5.203 inches and 5.328 inches

**Body Length:**

Between 4.344 inches and 4.438 inches

**Overall Diameter:**

7.500 inches

**Pressure Switch Type:**

Differential

**Mounting Facility Circle Radius:**

3.500 inches

**Mounting Method:**

Flange and threaded stud

**Features Provided:**

Calibrated scale

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Proof Pressure:**

500.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Four position circular

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+0.00/+50.00 actuation point inches of water

**Contact Adjustment Type:**

External actuation point screw with scale

**Contact Voltage Rating In Volts:**

30.0 dc at sea level fourth voltage

**Special Features:**

Square root scale, 0-25 gpm, graduations at 5 gpm intervals, 6 in. Diameter dial

**Thread Series Designator:**

Unc single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0