

View Online at <https://aerobasegroup.com/nsn/5930-01-047-7024>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

1.125 inches

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.500 inches single actuator

**Overall Diameter:**

0.500 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock flatted bushing at 9: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 highest dc voltage rating at sea level 6.0 lowest dc voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load ac at sea level 1.0 amperes resistive load highest dc voltage rating at sea level 1.0 amperes resistive load lowest dc voltage rating at sea level

**Precious Material And Location:**

Contacts and rotor blades silver and contact and rotor blade surfaces gold

**Precious Material:**

Silver and gold

**Style Designator:**

Miniature, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0