NSN 5930-01-047-7029

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-047-7029
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Moisture resistant
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.090 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Amber single actuator and white single actuator
Actuator Inscription:
Enable, inhibit single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.620 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes
inductive dc and 2.500 amperes lamp dc
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
5 tab, solder lug and 6 turret

N/a

Shelf Life:

NSN 5930-01-047-7029

Push Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A053a0