# NSN 5930-01-047-8049

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-047-8049

### Thread Class:

2a single mounting facility

#### Thread Length:

0.437 inches single mounting facility

## Hazardous Locations/environmental Protection:

Explosion proof

#### **Overall Length:**

2.937 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.437 inches single actuator

#### **Overall Diameter:**

Between 1.000 inches and 1.306 inches

#### **Individual Section Quantity:**

4

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

#### Operating Tempurature Range:

-65.0/+125.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

2 each section front

#### Throw Quantity:

2 each section rear

#### **Mounting Method:**

Threaded bushing w/panel seal single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device single actuator

### **Rotor Through Connection Quantity:**

2 each section

#### Switch Actuator Indexing Position Quantity:

2 single actuator

# NSN 5930-01-047-8049

Rotary Switch - Page 2 of 2



# Shaft Type: Round, flatted single actuator **Criticality Code Justification:** Feat **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks each section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Detent Rotational Torque Range:** +1.000/+4.500 inch-pounds single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 75.0 milliamperes resistive load ac at sea level **Special Features:** Item must comply with requirements of @desc production standard no. L02336; for navy nuclear propulsion plant products only Style Designator: Tap, circular, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0