NSN 5930-01-047-8940

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-047-8940

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.497 inches
Actuator Style:
Leaf
Actuator Width:
0.130 inches
Maximum Voltage Rating In Volts:
30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
7.0 grams
Switch Actuating Force:
40.0 grams
Actuator Movement:
Between 0.085 pretravel inches and 0.020 overtravel inches and 0.019 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 500.000 milliamperes inductive dc
Precious Material And Location:
Contact surfaces gold
Terminal Type And Quantity:
3 tab, solder lug

NSN 5930-01-047-8940

Sensitive Switch - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0