Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-047-9199

| Hazardous Locations/environmental Protection: | |
|---|---|
| Dustproof | |
| Overall Length: | |
| 6.000 inches | |
| Overall Height: | |
| 1.670 inches | |
| Overall Width: | |
| 1.920 inches | |
| Unthreaded Mounting Hole Diameter: | |
| 0.140 inches single mounting facility | |
| Individual Section Quantity: | |
| 8 | |
| Longest Horizontal Distance Between Mounting Centers: | |
| 5.735 inches single mounting facility | |
| Longest Vertical Distance Between Mounting Centers: | |
| 1.200 inches single mounting facility | |
| Mounting Method: | |
| Unthreaded hole single mounting facility | |
| Actuator Type: | |
| Thumbwheel all actuators | |
| Contact Voltage Rating In Volts: | |
| 28.0 dc at sea level | |
| Mounting Facility Pattern: | |
| Four position rectangular single mounting facility | |
| Switch Actuator Indexing Position Quantity: | |
| 10 all actuators | |
| Terminal Type: | |
| Printed circuit | |
| Contact Load Current Rating: | |
| 125.0 milliamperes resistive load dc at sea level | |
| Readout Indicator Marking: | |
| 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section | |
| Contact Arrangement Truth Table: | |
| Bcd, separate common to not-true bits, 2 pole - 10 positions each section | 1 |
| Color: | |
| White each indicator marking | |
| Style Designator: | |
| Rectangular inline indicating | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| | |

Code Indicating Wheel Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A052b0

