

View Online at <https://aerobasegroup.com/nsn/5930-01-047-9521>

Inside Diameter:

0.250 inches single connection

Overall Length:

4.875 inches

Overall Height:

4.562 inches

Overall Width:

2.875 inches

Body Length:

4.625 inches

Body Height:

2.500 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

1.750 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Proof Pressure:

400.00 pounds per square inch gage

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+60.00/+350.00 actuation point pounds per square inch and +36.00/+260.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Pressure Connector Type:

Quick disconnect, unthreaded internal single connection

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0