

View Online at <https://aerobasegroup.com/nsn/5930-01-048-0118>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.378 inches

Body Width:

0.406 inches

Body Height:

0.954 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.113 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.797 inches

Actuator Style:

Leaf

Actuator Free Position Height:

1.250 inches

Maximum Voltage Rating In Volts:

110.0 ac and 28.0 dc

End Application:

A and 10a weapon system

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

Between 8.0 ounces and 24.0 ounces

Actuator Movement:

Between 0.025 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0