# NSN 5930-01-048-0118

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-0118

## Body Style:

Hole mounted

## Hazardous Locations/environmental Protection:

Shock resistant

## Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

## **Body Length:**

1.378 inches

#### **Body Width:**

0.406 inches

#### **Body Height:**

0.954 inches

#### **Case Material:**

Plastic

#### **Unthreaded Mounting Hole Diameter:**

#### 0.113 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

## Actuator Length:

0.797 inches

## Actuator Style:

Leaf

#### Actuator Free Position Height:

1.250 inches

#### Maximum Voltage Rating In Volts:

110.0 ac and 28.0 dc

#### **End Application:**

A and 10a weapon system

#### Inclosure Type:

Hermetically sealed

#### Mounting Method:

Unthreaded hole

#### **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

3.0 ounces

## Switch Actuating Force:

Between 8.0 ounces and 24.0 ounces

## **Actuator Movement:**

Between 0.025 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000

amperes inductive ac and 3.000 amperes lamp ac

# NSN 5930-01-048-0118

Sensitive Switch - Page 2 of 2



## Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A053a0