

View Online at <https://aerobasegroup.com/nsn/5930-01-048-0122>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Explosion proof and humidity resistant

**Overall Length:**

3.635 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Body Width:**

0.625 inches

**Body Height:**

0.625 inches

**Case Material:**

Metal

**Actuator Length:**

0.530 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.120 inches

**Actuator Width:**

0.530 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Amber single actuator and amber single actuator

**Actuator Inscription:**

Oheat off single actuator

**Illuminated Actuator Color Sequence:**

Upper half of actuator amber lower half of actuator amber

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

3.375 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Full display lens

**Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Unable To Decode:**

Unable to decode and unable to decode

**Terminal Type And Quantity:**

1 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0