NSN 5930-01-048-0123

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-0123

Body Style:						
Panel mounted						
Hazardous Locations/environmental Protection:						
Explosion proof and humidity resistant						
Overall Length:						
3.635 inches						
Overall Height:						
0.750 inches						
Overall Width:						
0.750 inches						
Body Width:						
0.625 inches						
Body Height:						
0.625 inches						
Case Material:						
Metal						
Actuator Length:						
0.530 inches						
Actuator Style:						
Rectangular						
Actuator Height:						
0.100 inches						
Actuator Width:						
0.530 inches						
Actuator Color:						
Black single actuator						
Illuminated Actuator Color:						
Amber single actuator and green single actuator						
Actuator Inscription:						
Oheat oride single actuator						
Illuminated Actuator Color Sequence:						
Upper half of actuator amber lower half of actuator green						
Maximum Voltage Rating In Volts:						
115.0 ac and 28.0 dc						
Mounting Surface To Terminal End Distance:						
3.375 inches						
Inclosure Type:						
Fully enclosed						
Mounting Method:						
Panel						

Full display lens

Features Provided:

NSN 5930-01-048-0123

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

_		B4 - 4 -	!	AI	
М	recious	wate	eriai	Ana	Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0