

View Online at <https://aerobasegroup.com/nsn/5930-01-048-0123>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.635 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Case Material:

Metal

Actuator Length:

0.530 inches

Actuator Style:

Rectangular

Actuator Height:

0.100 inches

Actuator Width:

0.530 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Amber single actuator and green single actuator

Actuator Inscription:

Oheat oride single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator amber lower half of actuator green

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

3.375 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Full display lens

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0