NSN 5930-01-048-0123

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-0123

Body Style:				
Panel mounted				
Hazardous Locations/environmental Protection:				
Explosion proof and humidity resistant				
Overall Length:				
3.635 inches				
Overall Height:				
0.750 inches				
Overall Width:				
0.750 inches				
Body Width:				
0.625 inches				
Body Height:				
0.625 inches				
Case Material:				
Metal				
Actuator Length:				
0.530 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.100 inches				
Actuator Width:				
0.530 inches				
Actuator Color:				
Black single actuator				
Illuminated Actuator Color:				
Amber single actuator and green single actuator				
Actuator Inscription:				
Oheat oride single actuator				
Illuminated Actuator Color Sequence:				
Upper half of actuator amber lower half of actuator green				
Maximum Voltage Rating In Volts:				
115.0 ac and 28.0 dc				
Mounting Surface To Terminal End Distance:				
3.375 inches				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Panel				

Full display lens

Features Provided:

NSN 5930-01-048-0123

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

D!	NA-1:	AI I	
Precious	Materiai	And I	Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0