NSN 5930-01-048-0124

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-0124

View Online at https://aerobasegroup.com/nsn/5930-01-048-0124
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
0.880 inches
Overall Height:
1.470 inches
Overall Width:
0.880 inches
Bushing Length:
0.500 inches
Body Length:
0.464 inches
Actuator Diameter:
0.880 inches
Actuator Height:
0.238 inches
Maximum Voltage Rating In Volts:
120.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000
amperes inductive ac and 3.000 amperes lamp ac
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:

No

NSN 5930-01-048-0124Push Switch - Page 2 of 2



Fiig:

A053a0