## NSN 5930-01-048-0590

Pressure Switch - Page 1 of 2

pound



View Online at https://aerobasegroup.com/nsn/5930-01-048-0590

| Thread Class:   |
|---|
| 3b all pressure connection  |
| Inside Diameter:  |
| 0.250 inches all connections  |
| Overall Length:   |
| 3.000 inches  |
| Overall Height:   |
| 4.280 inches  |
| Overall Width:  |
| 4.250 inches  |
| Body Length:  |
| 3.000 inches  |
| Body Height:  |
| 3.000 inches  |
| Pressure Switch Type:   |
| Gage  |
| Operating Tempurature Rating:   |
| Between -65.0 degrees fahrenheit and 150.0 degrees fahrenheit   |
| Mounting Method:  |
| Input port  |
| Features Provided:  |
| Hermetically sealed case  |
| Thready Qty Per Inch (tpi):   |
| 28 all pressure connection  |
| Contact Action Stimulus:  |
| Increase  |
| Proof Pressure:   |
| 50.00 pounds per square inch  |
| Thread Size:  |
| 0.250 inches single pressure connection   |
| Nonpile-up Contact Arrangement:   |
| 1 pole, single throw, normally closed, momentary action   |
| Sensing Element Burst Pressure:   |
| 70.00 pounds per square inch  |
| Terminal Type:  |
| Wire lead   |
| Contact Load Current Rating:  |
| 80.0 milliamperes resistive load single voltage   |
| Contact Adjustability:  |
| Deactuation point not adjustable and actuation point not adjustable   |
| Contact Stimulus Rating:  |
| 280.00 actuation point centimeters per second per second and 125.00 deactuation point centimeters per second and 55.00 differential point |

## NSN 5930-01-048-0590

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type: Plain, threaded internal all connections Media For Which Designed: Liquid Style Designator: Rectangular Thread Series Designator: Unf all pressure connection Shelf Life: N/a Unit Of Measure:

**Demilitarization:** No

Fiig:

A048b0