

View Online at <https://aerobasegroup.com/nsn/5930-01-048-1669>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.373 inches and 0.377 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.090 inches

Actuator Length:

0.511 inches

Actuator Style:

Leaf

Actuator Width:

0.109 inches

Actuator Free Position Height:

Between 0.555 inches and 0.585 inches

Actuator Adapter Style:

Roller arm

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

6.0 ounces

Actuator Movement:

0.094 pretravel inches and 0.047 overtravel inches and 0.031 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0