## NSN 5930-01-048-1669

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-1669

| Body Style:  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| Hole mounted   |  |  |  |  |  |  |
| Hazardous Locations/environmental Protection:                                    |  |  |  |  |  |  |
| Dustproof  |  |  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:        |  |  |  |  |  |  |
| Between 0.373 inches and 0.377 inches  |  |  |  |  |  |  |
| Body Length:   |  |  |  |  |  |  |
| 0.781 inches   |  |  |  |  |  |  |
| Body Width:  |  |  |  |  |  |  |
| 0.250 inches   |  |  |  |  |  |  |
| Body Height:   |  |  |  |  |  |  |
| 0.359 inches   |  |  |  |  |  |  |
| Case Material:   |  |  |  |  |  |  |
| Plastic  |  |  |  |  |  |  |
| Unthreaded Mounting Hole Diameter:   |  |  |  |  |  |  |
| 0.090 inches   |  |  |  |  |  |  |
| Actuator Length:   |  |  |  |  |  |  |
| 0.511 inches   |  |  |  |  |  |  |
| Actuator Style:  |  |  |  |  |  |  |
| Leaf   |  |  |  |  |  |  |
| Actuator Width:  |  |  |  |  |  |  |
| 0.109 inches   |  |  |  |  |  |  |
| Actuator Free Position Height:   |  |  |  |  |  |  |
| Between 0.555 inches and 0.585 inches  |  |  |  |  |  |  |
| Actuator Adapter Style:  |  |  |  |  |  |  |
| Roller arm   |  |  |  |  |  |  |
| Maximum Voltage Rating In Volts:   |  |  |  |  |  |  |
| 28.0 dc  |  |  |  |  |  |  |
| Inclosure Type:  |  |  |  |  |  |  |
| Fully enclosed   |  |  |  |  |  |  |
| Nonpile-up Contact Arrangement:  |  |  |  |  |  |  |
| 1 pole, double throw, one position momentary single switch unit                  |  |  |  |  |  |  |
| Switch Release Force:  |  |  |  |  |  |  |
| 0.5 ounces   |  |  |  |  |  |  |
| Switch Actuating Force:  |  |  |  |  |  |  |
| 6.0 ounces   |  |  |  |  |  |  |
| Actuator Movement:   |  |  |  |  |  |  |
| 0.094 pretravel inches and 0.047 overtravel inches and 0.031 differential inches |  |  |  |  |  |  |
| Contact Load Current Rating At Maximum Rated Voltage:                            |  |  |  |  |  |  |
| 5 000 amperes resistive dc and 3 000 amperes inductive dc                        |  |  |  |  |  |  |

Terminal Type And Quantity:

3 tab, solder lug

## NSN 5930-01-048-1669

Sensitive Switch - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0