

View Online at <https://aerobasegroup.com/nsn/5930-01-048-1669>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.373 inches and 0.377 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.359 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.090 inches

**Actuator Length:**

0.511 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.109 inches

**Actuator Free Position Height:**

Between 0.555 inches and 0.585 inches

**Actuator Adapter Style:**

Roller arm

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

0.5 ounces

**Switch Actuating Force:**

6.0 ounces

**Actuator Movement:**

0.094 pretravel inches and 0.047 overtravel inches and 0.031 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0