# NSN 5930-01-048-1669

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-1669

## Body Style:

Hole mounted

## Hazardous Locations/environmental Protection:

Dustproof

## Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.373 inches and 0.377 inches

## **Body Length:**

0.781 inches

#### **Body Width:**

0.250 inches

#### **Body Height:**

0.359 inches

**Case Material:** 

Plastic

**Unthreaded Mounting Hole Diameter:** 

## 0.090 inches

Actuator Length:

0.511 inches

Actuator Style:

Leaf

## Actuator Width:

0.109 inches

## Actuator Free Position Height:

Between 0.555 inches and 0.585 inches

#### Actuator Adapter Style:

Roller arm

## Maximum Voltage Rating In Volts:

28.0 dc

#### Inclosure Type:

Fully enclosed

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

0.5 ounces

#### Switch Actuating Force:

6.0 ounces

## **Actuator Movement:**

0.094 pretravel inches and 0.047 overtravel inches and 0.031 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

 $5.000 \mbox{ amperes resistive dc}$  and  $3.000 \mbox{ amperes inductive dc}$ 

# Terminal Type And Quantity:

3 tab, solder lug

# NSN 5930-01-048-1669

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

