NSN 5930-01-048-2677

Hazardous Locations/environmental Protection:

Toggle Switch - Page 1 of 2

Body Style: Hole mount

Dustproof



View Online at https://aerobasegroup.com/nsn/5930-01-048-2677

Center To Center Distance Between Mounting Facilities Parallel To Length:

| 1.312 inches |
|--|
| Body Length: |
| 0.875 inches |
| Body Width: |
| 0.531 inches |
| Body Height: |
| 0.781 inches |
| Case Material: |
| Metal |
| Unthreaded Mounting Hole Diameter: |
| 0.141 inches |
| Actuator Length: |
| 0.781 inches |
| Actuator Style: |
| Rectangular |
| Actuator Width: |
| 0.406 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained |
| Actuator Position-locking Relationship: |
| Up position locked in and down position locked in |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 125.0 ac and 125.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 500.000 milliamperes resistive dc and 3.000 amperes resistive ac |
| Precious Material And Location: |
| Terminals and contact surfaces silver |
| Terminal Type And Quantity: |
| 6 tab, solder lug |

NSN 5930-01-048-2677

Toggle Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0