## NSN 5930-01-048-3321

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-3321

## **Body Style:**

Panel mounted

### Hazardous Locations/environmental Protection:

Moisture resistant

## **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Actuator Length:

0.620 inches

Actuator Style:

#### Rectangular

Actuator Height:

#### 0.090 inches

Actuator Width:

## 0.620 inches

Actuator Color:

White single actuator

### Illuminated Actuator Color:

Amber single actuator and white single actuator

#### **Actuator Inscription:**

Norm, fault single actuator

### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Mounting Surface To Terminal End Distance:

2.620 inches

#### Inclosure Type:

Fully enclosed

### **Mounting Method:**

Panel

#### **Features Provided:**

Rfi shielding

## Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc

inductive de and 2.500 amperes lamp

## Precious Material And Location:

Contacts silver

#### **Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

### Shelf Life:

N/a

# NSN 5930-01-048-3321

Push Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

