NSN 5930-01-048-4342

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Thread Class:

Body Style:Bushing mounted

Moisture proof

Overall Length:

1.847 inches

2a



View Online at https://aerobasegroup.com/nsn/5930-01-048-4342

| Body Diameter: |
|--|
| 0.625 inches |
| Bushing Length: |
| 0.560 inches |
| Body Length: |
| 0.670 inches |
| Overall Diameter: |
| 0.880 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.875 inches |
| Actuator Height: |
| 0.430 inches |
| Actuator Color: |
| Green single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Rfi shielding |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.625 inches |
| Nonpile-up Contact Arrangement: |
| 2 two circuit, double break/double make, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc |
| |

NSN 5930-01-048-4342Push Switch - Page 2 of 2



| Thread Series Designator: |
|-----------------------------|
| Uns |
| Terminal Type And Quantity: |
| 4 tab w/screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0