NSN 5930-01-048-4342

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Thread Class:

Body Style:Bushing mounted

Moisture proof

Overall Length:

1.847 inches

2a



View Online at https://aerobasegroup.com/nsn/5930-01-048-4342

Body Diameter:
0.625 inches
Bushing Length:
0.560 inches
Body Length:
0.670 inches
Overall Diameter:
0.880 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.875 inches
Actuator Height:
0.430 inches
Actuator Color:
Green single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Threaded bushing
Features Provided:
Rfi shielding
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

NSN 5930-01-048-4342Push Switch - Page 2 of 2



Thread Series Designator:
Uns
Terminal Type And Quantity:
4 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0