

View Online at <https://aerobasegroup.com/nsn/5930-01-048-6185>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

0.750 inches

**Body Length:**

0.875 inches

**Body Width:**

2.000 inches

**Body Height:**

0.687 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

0.875 inches

**Actuator Roller Diameter:**

0.437 inches

**Actuator Roller Width:**

0.167 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.468 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

30.0 ounces

**Actuator Movement:**

Between 0.065 pretravel inches and 0.188 overtravel inches and 0.660 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive ac

**Special Features:**

Temp tolerance up to 1000deg f

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0