NSN 5930-01-048-7546

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-7546

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
1.310 inches
Overall Height:
1.000 inches
Overall Width:
0.625 inches
Shaft Diameter:
0.205 inches single actuator
Shaft Length:
0.695 inches single actuator
Unthreaded Mounting Hole Diameter:
0.091 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
0.812 inches single mounting facility
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
End Application:
Control radio set
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section rear
Throw Quantity:
4 single section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:

Breaks before makes single section rear

NSN 5930-01-048-7546

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+8.000/+14.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0