NSN 5930-01-048-9294

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-9294

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof and corrosion resistant

Body Diameter:

0.780 inches

Bushing Length:

0.955 inches

Body Length:

1.000 inches

Case Material:

Plastic

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.485 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.120 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Aircraft, eagle f-15

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

32.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

Between 48.0 ounces and 96.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

NSN 5930-01-048-9294

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

Special Features:

Weapno system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A053a0