NSN 5930-01-048-9294

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-048-9294

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Dustproof and corrosion resistant
Body Diameter:
0.780 inches
Bushing Length:
0.955 inches
Body Length:
1.000 inches
Case Material:
Plastic
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.485 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.120 inches
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Aircraft, eagle f-15
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
32.0 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
Between 48.0 ounces and 96.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

NSN 5930-01-048-9294

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

Special Features:

Weapno system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A053a0