

View Online at <https://aerobasegroup.com/nsn/5930-01-049-1335>

Unthreaded Mounting Hole Diameter:

Between 0.219 inches and 0.233 inches

Longest Horizontal Distance Between Mounting Centers:

2.120 inches

Longest Vertical Distance Between Mounting Centers:

2.120 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -34.0 degrees celsius and 71.0 degrees celsius

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

18 all pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

400.0 milliamperes resistive load second voltage and 200.0 milliamperes inductive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

4.80 actuation point pounds per square inch

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

50.0 first voltage and 60.0 first voltage

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0