## NSN 5930-01-049-3684

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-049-3684

Hazardous Locations/environmental Protection:
Fungus resistant
Overall Length:
2.070 inches
Body Diameter:
0.550 inches
Body Length:
1.570 inches
Tempurature Sensing Element Type:
Internal sensor
Width Across Flats:
0.875 inches
Operating Tempurature Rating:
Between -20.0 degrees fahrenheit and 575.0 degrees fahrenheit
Mounting Method:
Threaded bushing
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
14 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
0.500 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, double break, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
1.5 amperes resistive load second voltage
Contact Adjustability:
Contact Adjustability:  Actuation point not adjustable and deactuation point not adjustable
Actuation point not adjustable and deactuation point not adjustable
Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating:
Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating:  160.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit
Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating:  160.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:
Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating:  160.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  240.0 ac at sea level second voltage
Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating:  160.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  240.0 ac at sea level second voltage  Media For Which Designed:
Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating:  160.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  240.0 ac at sea level second voltage  Media For Which Designed:  Gas or liquid
Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating:  160.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  240.0 ac at sea level second voltage  Media For Which Designed:  Gas or liquid  Style Designator:

## NSN 5930-01-049-3684

Thermostatic Switch - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0