

View Online at <https://aerobasegroup.com/nsn/5930-01-049-4840>

Thread Class:

3a single pressure connection

Thread Length:

0.437 inches single pressure connection

Overall Length:

2.750 inches

Outside Diameter:

0.125 inches single connection

Body Diameter:

1.875 inches

Body Length:

1.625 inches

Overall Diameter:

2.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Clamp

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

500.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

10.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

62.00 actuation point pounds per square inch and 42.00 deactuation point pounds per square inch and 20.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A048b0