## NSN 5930-01-049-5771

Sensitive Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-049-5771

Bushing mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
1.000 inches
Overall Height:
2.855 inches
Overall Width:
1.000 inches
Body Diameter:
1.000 inches
Bushing Length:
1.000 inches
Body Length:
1.750 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.380 inches
Actuator Free Position Height:
0.380 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 6.0 ounces and 12.0 ounces

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Actuator Movement:** 

## NSN 5930-01-049-5771

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

**Thread Series Designator:** 

Unef

**Terminal Type And Quantity:** 

6 screw

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0