NSN 5930-01-049-5771

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-049-5771

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

1.000 inches

Overall Height:

2.855 inches

Overall Width:

1.000 inches

Body Diameter:

1.000 inches

Bushing Length:

1.000 inches

Body Length:

1.750 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.380 inches

Actuator Free Position Height:

0.380 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 6.0 ounces and 12.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

NSN 5930-01-049-5771

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0