

View Online at <https://aerobasegroup.com/nsn/5930-01-049-7930>

**Overall Length:**

Between 2.399 inches and 2.574 inches

**First Flat Length:**

0.343 inches single actuator

**Flat Height:**

0.218 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.875 inches single actuator

**Overall Diameter:**

Between 1.000 inches and 1.306 inches

**Nonturn Device Radius:**

0.360 inches at 3: 00 o'clock and 0.390 inches at 3: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

11 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

11 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load dc at sea level and 1.0 amperes inductive load dc at sea level

**Special Features:**

Furnished w/clamp, strain relief, cable and connector

**Style Designator:**

Tap, circular, bushing mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0