

View Online at <https://aerobasegroup.com/nsn/5930-01-049-8273>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.188 inches single mounting facility

**Overall Length:**

1.937 inches

**Overall Height:**

1.359 inches

**Overall Width:**

1.500 inches

**First Flat Length:**

0.437 inches single actuator

**Flat Height:**

0.156 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.437 inches single actuator

**Nonturn Device Radius:**

0.438 inches at 3:00 o'clock and 0.438 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

240.0 highest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Quick disconnect, male

**Switch Actuator Positioning Increment:**

72.0 degrees single actuator

**Contact Load Current Rating:**

38.0 amperes motor load highest ac voltage rating at sea level

**Precious Material And Location:**

Terminals silver

**Precious Material:**

Silver

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0