

View Online at <https://aerobasegroup.com/nsn/5930-01-049-8273>

Thread Class:

2a single mounting facility

Thread Length:

0.188 inches single mounting facility

Overall Length:

1.937 inches

Overall Height:

1.359 inches

Overall Width:

1.500 inches

First Flat Length:

0.437 inches single actuator

Flat Height:

0.156 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.437 inches single actuator

Nonturn Device Radius:

0.438 inches at 3: 00 o'clock and 0.438 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

240.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Quick disconnect, male

Switch Actuator Positioning Increment:

72.0 degrees single actuator

Contact Load Current Rating:

38.0 amperes motor load highest ac voltage rating at sea level

Precious Material And Location:

Terminals silver

Precious Material:

Silver

Style Designator:

Tap, square frame

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0