

View Online at <https://aerobasegroup.com/nsn/5930-01-049-9261>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

1.640 inches

**First Flat Length:**

0.281 inches single actuator

**Flat Height:**

0.188 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.406 inches single actuator

**Overall Diameter:**

0.750 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 12: 00 o'clock

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

3 single section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

150.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+16.000/+36.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level and 125.0 milliamperes inductive load dc at sea level

**Precious Material And Location:**

Contacts and terminals silver

**Precious Material:**

Silver

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0