NSN 5930-01-050-0534

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-050-0534

Overall Length:

- 5.125 inches
- **Overall Height:**
- 5.938 inches

Overall Width:

- 2.625 inches
- **Body Length:**
- 5.000 inches

Body Height:

2.750 inches

Distance Between Mounting Facility Centers:

5.250 inches

End Application:

Landing craft utili type 98042

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Proof Pressure:

400.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+60.00/+350.00 actuation point pounds per square inch and +60.00/+350.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

NSN 5930-01-050-0534

Pressure Switch - Page 2 of 2



Pressure Connector Type:

Plain, threaded internal single connection

Special Features:

Special-adjustment differential

Media For Which Designed:

Gas

Precious Material:

Silver

Thread Series Designator:

F-ptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0