## 5



| <b>NSN 5930-01-050-4325</b><br>Thermostatic Switch - Page 1 of 2   | AeroBase<br>Group       |
|--|-------------------------|
| View Online at https://aerobasegroup.com/nsn/5930-01-050-4325  |                         |
| Overall Length:  |                         |
| 1.035 inches   |                         |
| Overall Height:  |                         |
| 0.300 inches   |                         |
| Body Diameter:   |                         |
| 0.660 centimeters  |                         |
| Mounting Slot Width:   |                         |
| 0.104 inches   |                         |
| Distance Between Mounting Facility Centers:  |                         |
| 0.937 inches   |                         |
| Tempurature Sensing Element Type:  |                         |
| Internal sensor  |                         |
| Mounting Method:   |                         |
| Bracket and slot   |                         |
| Features Provided:   |                         |
| Hermetically sealed case   |                         |
| Contact Action Stimulus:   |                         |
| Increase   |                         |
| Mounting Facility Pattern:   |                         |
| Two position in-line   |                         |
| Nonpile-up Contact Arrangement:  |                         |
| 1 pole, single throw, normally open, momentary action  |                         |
| Terminal Type:   |                         |
| Tab, solder lug  |                         |
| Contact Load Current Rating:   |                         |
| 2.0 amperes resistive load second voltage  |                         |
| Contact Adjustability:   |                         |
| Deactuation point not adjustable and actuation point not adjustable  |                         |
| Contact Stimulus Rating:   |                         |
| 102.00 actuation point degrees fahrenheit and 98.50 deactuation point degrees fahrenheit and 2.00 differential p | oint degrees fahrenheit |
| and 5.00 differential point degrees fahrenheit   |                         |
| Contact Voltage Rating In Volts:   |                         |
| 30.0 dc at sea level second voltage  |                         |
| Special Features:  |                         |
| Loose bracket  |                         |
| Frequency In Hertz:  |                         |
| 60.0 second voltage  |                         |
| Media For Which Designed:  |                         |

Gas or liquid

**Precious Material:** 

Silver

Style Designator:

Disc

## NSN 5930-01-050-4325

Thermostatic Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

