

View Online at <https://aerobasegroup.com/nsn/5930-01-050-4344>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.547 inches

Body Length:

0.781 inches

Body Width:

0.290 inches

Body Height:

0.927 inches

Case Material:

Metal

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.735 inches

Actuator Roller Diameter:

0.188 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Training devices 49956

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

1.5 ounces

Switch Actuating Force:

8.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0