## NSN 5930-01-050-4344

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-050-4344

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.547 inches
Body Length:
0.781 inches
Body Width:
0.290 inches
Body Height:
0.927 inches
Case Material:
Metal
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.735 inches
Actuator Roller Diameter:
0.188 inches
Actuator Roller Width:
0.125 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
End Application:
Training devices 49956
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Switch Release Force:
1.5 ounces
Switch Actuating Force:
8.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 10.000 amperes resistive ac

Contacts silver

**Precious Material And Location:** 

## NSN 5930-01-050-4344

Sensitive Switch - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

8 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0