NSN 5930-01-050-4345

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-050-4345

Body Style:
Bushing/hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Bushing Length:
0.375 inches
Body Length:
1.281 inches
Body Width:
0.375 inches
Body Height:
0.969 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.156 inches
Actuator Height:
0.291 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
End Application:
Training devices 49956
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Switch Release Force:
5.0 ounces
Switch Actuating Force:
Between 8.0 ounces and 16.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:

Precious Material And Location:

7.500 amperes inductive dc and 8.000 amperes resistive ac

Contacts silver

NSN 5930-01-050-4345 Sensitive Switch - Page 2 of 2



inread Series Designator:
Uns
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0