## NSN 5930-01-050-4345

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-050-4345

#### **Body Style:**

Bushing/hole mounted

## Hazardous Locations/environmental Protection:

Dustproof

## **Bushing Length:**

0.375 inches

## **Body Length:**

1.281 inches

#### **Body Width:**

0.375 inches

#### **Body Height:**

0.969 inches

#### **Case Material:**

Metal

#### **Actuator Style:**

## Round

## **Actuator Diameter:**

0.156 inches

## **Actuator Height:**

0.291 inches

## Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

## **End Application:**

Training devices 49956

#### **Inclosure Type:**

Fully enclosed

#### **Mounting Method:**

Threaded bushing

## Thready Qty Per Inch (tpi):

40

## **Thread Size:**

0.250 inches

#### Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

#### Switch Release Force:

5.0 ounces

#### Switch Actuating Force:

Between 8.0 ounces and 16.0 ounces

## Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes inductive dc and 8.000 amperes resistive ac

## **Precious Material And Location:**

Contacts silver

# NSN 5930-01-050-4345

Sensitive Switch - Page 2 of 2

**Thread Series Designator:** 

Uns

## Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A053a0

